

**WHAT IS CLAIMED IS:**

1. A mobile communication terminal including two lamps for incoming call notification, the terminal comprising:

two lamps for incoming call notification externally mounted on the mobile  
5 communication terminal, each of the lamps including a light emitting element; and  
display control means internally mounted on the mobile communication terminal for  
individually controlling the two lamps.

2. The mobile communication terminal as set forth in claim 1, further comprising:

a front folder including a center hinge arm;  
10 a rear folder including two side-hinge arms having an internal space of  
predetermined dimensions; and  
a hinge device mechanically connecting the front folder with the rear folder,  
said two lamps being provided on the side-hinge arms of the rear folder.

3. The mobile communication terminal as set forth in claim 1, wherein each of said  
15 two lamps includes a predetermined number of light emitting elements of different colors.

4. The mobile communication terminal as set forth in claim 3, wherein the display  
control means controls the two lamps to emit light alternately when an incoming call signal  
is received.

678- 1133 (P10749)

5. A method for providing GPS services using a mobile communication terminal which includes two lamps for incoming call notification, the method comprising the steps of:

- a) receiving GPS information from a GPS service provider;
- b) extracting left-turn and right-turn information from the GPS information; and
- 5 c) activating the two lamps as left and right lamps in concert with the extracted left-turn and right-turn information to provide navigation direction.

6. The method as set forth in claim 5, further comprising the steps of:

- d) checking whether a call signal for establishing a call connection is received;
- e) if the checked result of step d) is that the call signal is received, checking whether
- 10 GPS information is currently displayed through the two lamps;
- f) if the checked result of step e) is that a first lamp of the two lamps currently displays GPS information including left-turn or right-turn information, allowing a second lamp of the two lamps to emit light that is a different color than the color of said first lamp; and
- 15 g) if the checked result of step e) is that the two lamps are not displaying GPS information, operating the two lamps in a normal incoming call notification mode.

7. The method as set forth in claim 5, wherein the steps are performed using an external display device interconnected with the two lamps, the external display device being mounted on a cradle of the mobile communication terminal.

20 8. The method as set forth in claim 5, wherein the steps are performed using an external display device interconnected with the two lamps, the external display device being

externally mounted on the mobile communication terminal.